

CLEANING TIPS

Please inspect your sauna once a week and make sure any damage is repaired immediately. If any screws are loose, for example, tighten them straight away. Limescale or water spots on the sauna heater can be removed with a brush. After cleaning your sauna, please air it thoroughly.

In a commercially used sauna, the interior panelling should be replaced every five to seven years.

Please observe the following rules for keeping a public sauna clean:

CLEANING THE FLOOR

The floor of the sauna should be cleaned daily. Particular care should be taken around the feet of the benches. The floor should be scrubbed if necessary.

ATTENTION!

The wood inside a sauna is very dry, and hence very sensitive to moisture. So never use a hose or power washer on the panelling or benches in the sauna. Hoses and power washers must also not be used on the exterior panelling of a sauna.

Please note that any warranty claims shall be null and void if a power washer or hose is used on the sauna.

The entire floor area of the PROFESSIONAL sauna is accessible, or can be accessed easily by folding up or removing the benches or seats.

In sauna cabins where the benches or seats are supported by a conventional timber substructure, the floor should be cleaned thoroughly with a damp mop – but not dripping wet – particularly around the feet of the benches. However, the floor must not be hosed down, or the wood could get wet and split.

SEAT & BENCHES

Once or twice a year – or more frequently if the sauna is used heavily – sand down the top of the benches in the sauna, using very light sandpaper. The benches should be wiped down regularly with a disinfectant. We recommend diluted hydrogen peroxide (3% concentration).

ATTENTION!

Disinfectants are highly corrosive, so please take all regular precautions when using such in the sauna! Hydrogen peroxide does not leave any toxic residue. It decomposes into oxygen and water when it comes into contact with organic materials.

WALL PANELS

The exterior walls of your sauna can be oiled with Cabots Natural decking to protect them against moisture. Do not oil or paint the interior panelling or any of the interior fittings of your sauna. Once or

twice a year, or more frequently if the sauna is used heavily, you should wipe the walls and ceiling of your sauna with a damp – not wet! –cloth (do NOT hose down!).

DOOR

Check the screws on the door handles regularly and tighten if necessary. Oil the door hinges regularly. Oil the safety catch on the door regularly, and adjust if necessary.

REPLACING THE SAUNA STONES

In a commercially used sauna – or if you use your private sauna on a daily basis – we recommend you renew the sauna stones once a year. <https://www.youtube.com/watch?v=FCQz-KtzYIc&t=14s>

GENERAL INFORMATION

Recommended: Affix a board (or several boards) displaying the sauna rules in a prominent place on or close to your sauna.

[Type here]

1/77 Mihini Road, Swanson, Auckland 0610 email: sales@nzsauna.co.nz Web www.nzsauna.co.nz Ph 09-8385867